

10/520479

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
19 February 2004 (19.02.2004)

PCT

(10) International Publication Number
WO 2004/015887 A1

(51) International Patent Classification⁷: **H04B 7/10, 7/06**

(21) International Application Number:

PCT/IB2002/003029

(22) International Filing Date: 5 August 2002 (05.08.2002)

(25) Filing Language:

English

(26) Publication Language:

English

(71) Applicant (for all designated States except US): **NOKIA CORPORATION** [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **HÄMÄLÄINEN, Jyri, K.** [FI/FI]; Niskantie 18, FIN-90160 Oulu (FI). **WICHMAN, Risto** [FI/FI]; Viipurinkatu 10 A 20, FIN-00510 Helsinki (FI).

(74) Agents: **LESON, Thomas, Johannes, Alois et al.**; TBK-Patent, Bavariaring 4-6, 80336 München (DE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **TRANSMISSION DIVERSITY WITH TWO CROSS-POLARISED ANTENNAS ARRAYS**



(57) Abstract: The present invention concerns a method for selecting a diversity mode (A, B, C) to be applied by a transmitter having two cross-polarized antenna arrays (Ant1, Ant 2), each representing a diversity branch, comprising the steps of: providing (S10) a plurality of diversity mode performance chart look-up tables (LUT, LUT1, LUT2, LUT3), mapping a respective individual diversity mode (A, B, C) to a respective pair of time correlation value (TC) and space correlation value (SC) for said two cross-polarized antenna array beams, wherein a respective individual diversity mode is presented by a mapping area, wherein the plurality of performance chart look-up tables is parameterized by an indication of a ratio (P1/P2) of received powers from said diversity branches, first selecting (S13) one of said performance chart look-up tables dependent on determined ratio (P1/P2) of received powers from separate beams, and second selecting (S14) one of said individual diversity modes (A, B, C) according to the mapping to the determined actual time 303 relation (TC) and space correlation (SC) values from said first selected performance chart look-up table.

WO 2004/015887 A1